
KOMADA[®]

157)

KOMADA CBD15-E /20-E type is Fully Auto hand pallet truck. It adopts the advanced structure such as ring rod lifting system and DC controller, at same time it is equipped with high quality motor, traction battery and pump station motor. It has the characteristics of superior performance, convenient operation, flexible steering, reliable braking, good dynamic performance, less noise, less pollution and beautiful appearance.



CBD20-E Operating handle



Electromagnetic brake Brake type CBD15-E Operating handle Drive motor kW 0.75 Lift motor kW 8.0 Battery (according to DIN 43531/35/36) No Battery voltage / rate capacity V/Ah 24/20 24/30 24/40 48/15 48/20 Battery weight (±5%) 7.0 8.2 8.2 kg Type of drive control DC Noise level dB(A) ≤70 Mechanical Steering type Product colours depends on stock: red / yellow. CDB20-E - Hydraulic pump type CDB15-E - Hydraulic pump type

FULLY AUTO HAND PALLET TRUCK

kg

mm

 $\mathsf{m}\mathsf{m}$

mm

mm

mm

mm

mm

Wa

km/h

%

Product code

Manner of operation

Distance between fork backrest and front (x)

Qty of wheel, Front / Rear (x=driving wheel)

Height of handle in operation position (h14)

Service weight (without battery)

Load capacity (Q)

Load centre (c)

Wheel base (y)

Tire material

Driving wheel

Bearing wheel

Tread (b11)

Lifting height (h3)

Overall length (I1)

Overall width (b1 / b2)

Ground clearance under mast (m2)

Aisle width for pallets 1000*1200 crossways

Aisle width for pallets 1000*1200 lengthways

Body length (I2)

Fork size (s/e/l)

Fork width (b5)

Turning radius

Driving speed (load/unload)

Maximum gradeability (load/unload)

(Ast)

(Ast)

Lowered fork height (h13)

Drive type

CBD15-E

137

Electric

Tramp type

600

944

1243

PU

Ø210 x 70

Ø80 x 60

1x/4

535

200

740/1160

85

1603

453

685

50/150/1150

685

35

1804

1854

1398

4.2/4.5

5/10

CBD20-E

2000

146

^{*} Materials & specifications are subject to change without prior notice.